

## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### 3-D Laserscanning Entspiegelungsspray

Revision date: 31.05.2017

Page 1 of 10

#### SECTION 1: Identification of the substance/mixture and of the company/undertaking

##### 1.1. Product identifier

3-D Laserscanning Entspiegelungsspray

##### **Further trade names**

Article no. (user):

119.990.001

119.990.004

##### 1.2. Relevant identified uses of the substance or mixture and uses advised against

##### **Use of the substance/mixture**

Testing and measurement technology

##### 1.3. Details of the supplier of the safety data sheet

Company name:

Helling GmbH

Street:

Spoekerdamm 2

Place:

D-25436 Heidgraben

Telephone:

+49-4122-922-0

Telefax: +49-4122-922-201

e-mail:

info@helling.de

Internet:

www.helling.de

##### 1.4. Emergency telephone number:

GIZ Nord Göttingen +49-(0)511-19240  
(Information in German and English)

#### SECTION 2: Hazards identification

##### 2.1. Classification of the substance or mixture

##### **Regulation (EC) No. 1272/2008**

Hazard categories:

Aerosol: Aerosol 1

Serious eye damage/eye irritation: Eye Irrit. 2

Specific target organ toxicity - single exposure: STOT SE 3

Hazard Statements:

Extremely flammable aerosol.

Pressurised container: May burst if heated.

Causes serious eye irritation.

May cause drowsiness or dizziness.

##### 2.2. Label elements

##### **Regulation (EC) No. 1272/2008**

##### **Hazard components for labelling**

propan-2-ol; isopropyl alcohol; isopropanol

**Signal word:**

Danger

**Pictograms:**

##### **Hazard statements**

H222

Extremely flammable aerosol.

H229

Pressurised container: May burst if heated.

H319

Causes serious eye irritation.

H336

May cause drowsiness or dizziness.

##### **Precautionary statements**

P102

Keep out of reach of children.

## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### 3-D Laserscanning Entspiegelungsspray

Revision date: 31.05.2017

Page 2 of 10

P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P211	Do not spray on an open flame or other ignition source.
P251	Do not pierce or burn, even after use.
P271	Use only outdoors or in a well-ventilated area.
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P410+P412	Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.
P501	Dispose of contents/container to industrial incineration plant.

#### 2.3. Other hazards

No information available.

### SECTION 3: Composition/information on ingredients

#### 3.2. Mixtures

##### Hazardous components

CAS No	Chemical name			Quantity
	EC No	Index No	REACH No	
	Classification according to Regulation (EC) No. 1272/2008 [CLP]			
106-97-8	butane			50 - 60 %
	203-448-7	601-004-00-0	01-2119474691-32	
	Flam. Gas 1; H220			
74-98-6	propane			20 - 25 %
	200-827-9	601-003-00-5	01-2119486944-21	
	Flam. Gas 1; H220			
67-63-0	propan-2-ol; isopropyl alcohol; isopropanol			10 - 20 %
	200-661-7	603-117-00-0	01-2119457558-25	
	Flam. Liq. 2, Eye Irrit. 2, STOT SE 3; H225 H319 H336			
75-28-5	isobutane			2 - 4 %
	200-857-2	601-004-00-0		
	Flam. Gas 1; H220			

Full text of H and EUH statements: see section 16.

### SECTION 4: First aid measures

#### 4.1. Description of first aid measures

##### General information

First aider: Pay attention to self-protection!

##### After inhalation

Provide fresh air. In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible).

##### After contact with skin

Wash with plenty of water. Change contaminated clothing.

##### After contact with eyes

If product gets into the eye, keep eyelid open and rinse immediately with large quantities of water, for at least 5 minutes. Subsequently consult an ophthalmologist.

##### After ingestion

Rinse mouth immediately and drink plenty of water. Medical treatment necessary.

## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### 3-D Laserscanning Entspiegelungsspray

Revision date: 31.05.2017

Page 3 of 10

#### **4.2. Most important symptoms and effects, both acute and delayed**

Following inhalation: Headache. drowsiness. Dizziness.

#### **4.3. Indication of any immediate medical attention and special treatment needed**

Treat symptomatically.

### **SECTION 5: Firefighting measures**

#### **5.1. Extinguishing media**

##### **Suitable extinguishing media**

Co-ordinate fire-fighting measures to the fire surroundings.

#### **5.2. Special hazards arising from the substance or mixture**

Vapours may form explosive mixtures with air. Heating causes rise in pressure with risk of bursting.

#### **5.3. Advice for firefighters**

In case of fire: Wear self-contained breathing apparatus.

#### **Additional information**

Suppress gases/vapours/mists with water spray jet. Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

### **SECTION 6: Accidental release measures**

#### **6.1. Personal precautions, protective equipment and emergency procedures**

Remove all sources of ignition. Provide adequate ventilation. Do not breathe gas/vapour/aerosol. Avoid contact with skin, eyes and clothes.

#### **6.2. Environmental precautions**

Do not allow uncontrolled discharge of product into the environment.

#### **6.3. Methods and material for containment and cleaning up**

Ventilate affected area.

Flammable liquids: Absorb with liquid-binding material (e.g. sand, diatomaceous earth, acid- or universal binding agents).

#### **6.4. Reference to other sections**

Treat the recovered material as prescribed in the section on waste disposal.

### **SECTION 7: Handling and storage**

#### **7.1. Precautions for safe handling**

##### **Advice on safe handling**

If handled uncovered, arrangements with local exhaust ventilation have to be used. Do not breathe gas/fumes/vapour/spray. Avoid contact with skin, eyes and clothes.

##### **Advice on protection against fire and explosion**

Keep away from sources of ignition - No smoking. Take precautionary measures against static discharges. Vapours may form explosive mixtures with air.

#### **7.2. Conditions for safe storage, including any incompatibilities**

##### **Requirements for storage rooms and vessels**

Keep container tightly closed. Keep in a cool, well-ventilated place. Keep away from sources of ignition - No smoking.

##### **Advice on storage compatibility**

Do not store together with: Oxidising agent

#### **7.3. Specific end use(s)**

Inspection of metal surfaces

### **SECTION 8: Exposure controls/personal protection**

## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### 3-D Laserscanning Entspiegelungsspray

Revision date: 31.05.2017

Page 4 of 10

#### 8.1. Control parameters

##### Exposure limits (EH40)

CAS No	Substance	ppm	mg/m <sup>3</sup>	fibres/ml	Category	Origin
106-97-8	Butane	600	1450		TWA (8 h)	WEL
		750	1810		STEL (15 min)	WEL
67-63-0	Propan-2-ol	400	999		TWA (8 h)	WEL
		500	1250		STEL (15 min)	WEL

#### 8.2. Exposure controls



##### Appropriate engineering controls

If handled uncovered, arrangements with local exhaust ventilation have to be used. Do not breathe gas/fumes/vapour/spray.

##### Protective and hygiene measures

Remove contaminated, saturated clothing immediately. When using do not eat or drink. After work, wash hands and face.

##### Eye/face protection

Wear eye/face protection.

##### Hand protection

The quality of the protective gloves resistant to chemicals must be chosen as a function of the specific working place concentration and quantity of hazardous substances.

Recommended protective gloves brand: (Break through time > 480 min)

NBR (Nitrile rubber). (0,35 mm)

Butyl rubber. (0,5 mm)

FKM (fluororubber). (0,4 mm)

Recommended protective gloves brand: (Break through time > 240minutes.)

CR (polychloroprenes, Chloroprene rubber). (0,5 mm)

Unsuitable material:

NR (Natural rubber (Caoutchouc), Natural latex). PVC (Polyvinyl chloride).

For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

Protect skin by using skin protective cream.

##### Skin protection

Body protection: not required.

##### Respiratory protection

With correct and proper use, and under normal conditions, breathing protection is not required.

Respiratory protection necessary at: exceeding exposure limit values

Suitable respiratory protection apparatus: Filter type: A (colour: brown)

##### Environmental exposure controls

No information available.

## SECTION 9: Physical and chemical properties

#### 9.1. Information on basic physical and chemical properties

Physical state: Aerosol  
 Colour: white

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

**3-D Laserscanning Entspiegelungsspray**

Revision date: 31.05.2017

Page 5 of 10

Odour: characteristic

**Test method**

pH-Value: not determined

**Changes in the physical state**

Melting point: not determined

Initial boiling point and boiling range: not determined

Flash point: not determined

**Flammability**

Solid: not applicable

Gas: not applicable

**Explosive properties**

Heating causes rise in pressure with risk of bursting. Vapours may form explosive mixtures with air.

Lower explosion limits: not determined

Upper explosion limits: not determined

**Auto-ignition temperature**

Solid: not applicable

Gas: not applicable

Decomposition temperature: not determined

**Oxidizing properties**

Not oxidising.

Vapour pressure: not determined

Density (at 20 °C): 0,925 g/cm<sup>3</sup>

Water solubility: slightly soluble

**Solubility in other solvents**

not determined

Partition coefficient: not determined

Vapour density: not determined

Evaporation rate: not determined

**9.2. Other information**

Solid content: ~10%

**SECTION 10: Stability and reactivity****10.1. Reactivity**

No risks worthy of mention.

**10.2. Chemical stability**

No risks worthy of mention.

**10.3. Possibility of hazardous reactions**

Vapours may form explosive mixtures with air.

**10.4. Conditions to avoid**

Remove all sources of ignition. Keep away from heat.

**10.5. Incompatible materials**

Oxidizing agents.

**10.6. Hazardous decomposition products**

Carbon dioxide. Carbon monoxide.

## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### 3-D Laserscanning Entspiegelungsspray

Revision date: 31.05.2017

Page 6 of 10

## SECTION 11: Toxicological information

### 11.1. Information on toxicological effects

#### Acute toxicity

Based on available data, the classification criteria are not met.

#### ATEmix calculated

ATE (inhalative gas) 1468,7 ppm

CAS No	Chemical name				
	Exposure route	Dose	Species	Source	Method
106-97-8	butane				
	inhalative (4 h) aerosol	LC50 658 mg/l	Rat		
74-98-6	propane				
	inhalative (4 h) vapour	LC50 > 20 mg/l	Rat		
67-63-0	propan-2-ol; isopropyl alcohol; isopropanol				
	oral	LD50 4570 mg/kg	Rat		
	dermal	LD50 13400 mg/kg	Rabbit		
	inhalative (4 h) aerosol	LC50 30 mg/l	Rat		

#### Irritation and corrosivity

Irritant effect on the skin: Not an irritant.

Irritant effect on the eye: irritant.

#### Sensitising effects

No sensitizing effect known.

#### Carcinogenic/mutagenic/toxic effects for reproduction

According to current knowledge not a carcinogen. According to current knowledge not mutagen. According to current knowledge not reproduction toxic.

#### STOT-single exposure

May cause drowsiness or dizziness.

#### STOT-repeated exposure

No information available.

#### Aspiration hazard

Based on available data, the classification criteria are not met.

## SECTION 12: Ecological information

### 12.1. Toxicity

Aquatic toxicity: No data available

# Safety Data Sheet

according to Regulation (EC) No 1907/2006

## 3-D Laserscanning Entspiegelungsspray

Revision date: 31.05.2017

Page 7 of 10

CAS No	Chemical name					
	Aquatic toxicity	Dose	[h]   [d]	Species	Source	Method
74-98-6	propane					
	Acute fish toxicity	LC50 > 100 mg/l	96 h			
	Acute algae toxicity	ErC50 > 100 mg/l				
	Acute crustacea toxicity	EC50 > 100 mg/l	48 h			
67-63-0	propan-2-ol; isopropyl alcohol; isopropanol					
	Acute fish toxicity	LC50 8970 mg/l	96 h	Leuciscus idus (golden orfe)		
	Acute algae toxicity	ErC50 >1000 mg/l	72 h	Scenedesmus subspicatus		
	Acute crustacea toxicity	EC50 >1000 mg/l	48 h	Daphnia magna		
	Acute bacteria toxicity	(>100 mg/l)				

### 12.2. Persistence and degradability

The product has not been tested.

### 12.3. Bioaccumulative potential

The product has not been tested.

### Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
106-97-8	butane	2,89
74-98-6	propane	2,36
75-28-5	isobutane	2,8

### 12.4. Mobility in soil

The product has not been tested.

### 12.5. Results of PBT and vPvB assessment

not applicable

### 12.6. Other adverse effects

No information available.

### Further information

Do not allow to enter into surface water or drains. Do not allow to enter into soil/subsoil.

## SECTION 13: Disposal considerations

### 13.1. Waste treatment methods

#### Advice on disposal

Do not allow to enter into surface water or drains. Dispose of waste according to applicable legislation.

#### Waste disposal number of waste from residues/unused products

160504 WASTES NOT OTHERWISE SPECIFIED IN THE LIST; gases in pressure containers and discarded chemicals; gases in pressure containers (including halons) containing hazardous substances  
Classified as hazardous waste.

#### Waste disposal number of contaminated packaging

150104 WASTE PACKAGING; ABSORBENTS, WIPING CLOTHS, FILTER MATERIALS AND PROTECTIVE CLOTHING NOT OTHERWISE SPECIFIED; packaging (including separately collected municipal packaging waste); metallic packaging

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

**3-D Laserscanning Entspiegelungsspray**

Revision date: 31.05.2017

Page 8 of 10

**Contaminated packaging**

Wash with plenty of water. Completely emptied packages can be recycled.

**SECTION 14: Transport information****Land transport (ADR/RID)**

**14.1. UN number:** UN 1950  
**14.2. UN proper shipping name:** AEROSOLS  
**14.3. Transport hazard class(es):** 2  
Hazard label: 2.1



Classification code: 5F  
Special Provisions: 190 327 344 625  
Limited quantity: 1 L  
Transport category: 2  
Tunnel restriction code: D

**Other applicable information (land transport)**

EQ: E0

**Inland waterways transport (ADN)**

**14.1. UN number:** UN 1950  
**14.2. UN proper shipping name:** AEROSOLS  
**14.3. Transport hazard class(es):** 2  
Hazard label: 2.1



Classification code: 5F  
Special Provisions: 190 327 344 625  
Limited quantity: 1 L

**Other applicable information (inland waterways transport)**

EQ: E0

**Marine transport (IMDG)**

**14.1. UN number:** UN 1950  
**14.2. UN proper shipping name:** AEROSOLS  
**14.3. Transport hazard class(es):** 2.1  
**14.4. Packing group:** -  
Hazard label: 2.1



Special Provisions: 63, 190, 277, 327, 344, 959  
Limited quantity: See SP277  
EmS: F-D, S-U

**Other applicable information (marine transport)**

EQ: E0

**Air transport (ICAO-TI/IATA-DGR)**



**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

**3-D Laserscanning Entspiegelungsspray**

Revision date: 31.05.2017

Page 9 of 10

<b>14.1. UN number:</b>	UN 1950
<b>14.2. UN proper shipping name:</b>	AEROSOLS, flammable
<b>14.3. Transport hazard class(es):</b>	2.1
Hazard label:	2.1



Special Provisions:	A145 A167 A802
Limited quantity Passenger:	30 kg G
IATA-packing instructions - Passenger:	203
IATA-max. quantity - Passenger:	75 kg
IATA-packing instructions - Cargo:	203
IATA-max. quantity - Cargo:	150 kg

**Other applicable information (air transport)**Passenger-LQ: Y203  
EQ: E0**14.5. Environmental hazards**

ENVIRONMENTALLY HAZARDOUS: no

**14.6. Special precautions for user**

No information available.

**14.7. Transport in bulk according to Annex II of Marpol and the IBC Code**

not applicable

**SECTION 15: Regulatory information****15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture****EU regulatory information**

Restrictions on use (REACH, annex XVII):

Entry 28: butane; isobutane

2004/42/EC (VOC): 56 % (518 g/l)

**National regulatory information**

Employment restrictions: Observe restrictions to employment for juvenils according to the 'juvenile work protection guideline' (94/33/EC).

Water contaminating class (D): 1 - slightly water contaminating

**15.2. Chemical safety assessment**For the following substances of this mixture a chemical safety assessment has been carried out:  
propan-2-ol; isopropyl alcohol; isopropanol**SECTION 16: Other information****Changes**

section 1, 3, 7, 8, 11, 12, 15

**Abbreviations and acronyms**ADR: Accord européen sur le transport des marchandises dangereuses par Route  
(European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonized System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

**3-D Laserscanning Entspiegelungsspray**

Revision date: 31.05.2017

Page 10 of 10

CAS: Chemical Abstracts Service

LC50: Lethal concentration, 50%

LD50: Lethal dose, 50%

**Relevant H and EUH statements (number and full text)**

H220	Extremely flammable gas.
H222	Extremely flammable aerosol.
H225	Highly flammable liquid and vapour.
H229	Pressurised container: May burst if heated.
H319	Causes serious eye irritation.
H336	May cause drowsiness or dizziness.

**Further Information**

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

---

*(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)*